

MATERIAL SAFETY DATA SHEET ****

Phone#: (715) 723-4915

HIGH SIERRA CHEMICALS
P.O. BOX 848
CHIPPEWA FALLS, WI 54729

Latest Revision Date...03/01/11
Print Date.....03/16/11
EMERGENCY PHONE NUMBER: 1-800-424-9300

GREEN POWER

=====
SECTION 1 PRODUCT IDENTIFICATION
=====

PRODUCT NAME OR NUMBER..... GREEN POWER
TRADE NAME OR CHEMICAL NAME..... GREEN POWER
SYNONYMS..... N/A
FORMULA..... PROPRIETARY
CHEMICAL FAMILY..... CLEANER
MOLECULAR WEIGHT..... N/A
NFPA..... SEE SECTION 8
HMIS RATING..... SEE SECTION 8

=====
SECTION 2 HAZARDOUS INGREDIENTS / HAZARD DATA
=====

<u>CHEMICAL NAME(S)</u>	<u>CAS NUMBER</u>	<u>% WT</u>	<u>TLV-ACGIH</u>	<u>PEL-OSHA</u>	<u>SEC. 313</u>	<u>NTP</u>	<u>IARC</u>	<u>PROP. 65</u>
GLYCOL ETHER EB	111-76-2	<10	25 PPM	25 PPM	Yes	NO	NO	No
SODIUM HYDROXIDE	1310-73-2	<5	2 MG/M3	2 MG/M3	No	NO	NO	No

=====
SECTION 3 REGULATORY DATA
=====

NTP..... NATIONAL TOXICOLOGY PROGRAM
IARC..... INTERNATIONAL AGENCY FOR RESEARCH ON CANCER
PROPOSITION 65..... THIS PRODUCT CONTAINS INGREDIENTS ON
THE LIST OF PROPOSITION 65.
STATE OF CALIFORNIA SAFE DRINKING WATER AND
TOXIC ENFORCEMENT ACT OF 1986.
SECTION 313 SARA TITLE III... THE CHEMICAL(S) MARKED WITH A "YES" ON
SECTION 313 ARE SUBJECT TO THE REPORTING
REQUIREMENTS OF THIS SECTION.

=====
SECTION 4 PHYSICAL DATA
=====

BOILING/MELTING POINT @760 mm Hg ≥212°F
pH..... 13.1
SPECIFIC GRAVITY OR BULK DENSITY 1.031
SOLUBILITY IN WATER..... COMPLETE
APPEARANCE..... CLEAR GREEN/YELLOW
ODOR..... GLYCOL

=====
SECTION 5 FIRE AND EXPLOSION HAZARD DATA
=====

FLASH POINT °F (Test Method).... N/A
AUTOIGNITION TEMPERATURE..... N/A
FLAMMABILITY LIMITS IN AIR (% V) NOT DETERMINED
EXTINGUISHING MEDIA..... WATER, CARBON DIOXIDE, FOAM, DRY CHEMICAL
SPECIAL FIRE FIGHTING PROCEDURES WEAR SELF CONTAINED BREATHING APPARATUS &
FULL PROTECTIVE EQUIPMENT.
UNUSUAL FIRE & EXPLOSION HAZARDS EXTINGUISH ALL NEARBY SOURCES OF IGNITION.

GREEN POWER

=====
SECTION 6 HEALTH HAZARD DATA * EFFECTS OF OVEREXPOSURE
=====

THRESHOLD LIMIT VALUE.....SEE SECTION 2

SIGN AND SYMPTOMS OF EXPOSURE


EYES.....DIRECT CONTACT WITH CONCENTRATED PRODUCT MAY CAUSE MODERATE IRRITATION AND TEARING.
SKIN.....REPEATED OR PROLONGED CONTACT MAY CAUSE IRRITATION OR DRYING.
INHALATION.....BREATHING DUST OR MIST MAY IRRITATE THE NOSE AND THROAT.
INGESTION.....SWALLOWING LARGE QUANTITIES MAY CAUSE NAUSEA, VOMITING, DIARRHEA AND ABDOMINAL PAIN.
CHRONIC OVEREXPOSURE.....NONE KNOWN

=====
SECTION 7 EMERGENCY AND FIRST AID PROCEDURES
=====

INHALATION.....MOVE SUBJECT TO FRESH AIR. IF BREATHING IS DIFFICULT, OBTAIN MEDICAL HELP.
EYES.....FLUSH EYES WITH A LARGE AMOUNT OF WATER FOR AT LEAST 15 MINUTES. CONSULT A PHYSICIAN IF IRRITATION PERSISTS.
SKIN.....WASH AFFECTED SKIN AREAS WITH WATER. CONSULT PHYSICIAN IF IRRITATION PERSISTS.
INGESTION.....NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. DO NOT INDUCE VOMITING. GIVE LARGE QUANTITIES OF WATER. GET MEDICAL ATTENTION IMMEDIATELY.

=====
SECTION 8 HMS RATING SYSTEM
=====

NFPA
===



HMS RATING
=====

HEALTH HAZARD.....	1
FIRE HAZARD.....	0
REACTIVITY.....	0
PERSONAL PROTECTION....	SEE SECTION 10

=====
SECTION 9 REACTIVITY DATA
=====

PRODUCT STABILITY..... STABLE
Conditions to Avoid.....
CHEMICAL INCOMPATIBILITY..... STRONG ACID, ACID VAPOR. MAY PRODUCE CARBON DIOXIDE, CARBON MONOXIDE.
HAZARDOUS DECOMPOSITION PRODUCTS N/D
HAZARDOUS POLYMERIZATION..... WILL NOT OCCUR
Conditions to Avoid..... EXTREME HEAT, SPARK, OPEN FLAME
CORROSIVE TO METAL..... NO
OXIDIZER..... NO

=====
SECTION 10 SPECIAL PROTECTION INFORMATION
=====

RESPIRATORY PROTECTION.....NOT NEEDED

VENTILATION:

LOCAL EXHAUST.....NEEDED

